


(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number  
WO 01/99435 A2

- (51) International Patent Classification<sup>7</sup>: H04N 544/ (74) Agents: PRATT, John, S. et al.; KILPATRICK STOCKTON LLP, 1100 Peachtree Street, Suite 2800, Atlanta, GA 30309-4530 (US).
- (21) International Application Number: PCT/US01/08465
- (22) International Filing Date: 16 March 2001 (16.03.2001) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/213,058 21 June 2000 (21.06.2000) US  
60/214,529 27 June 2000 (27.06.2000) US  
60/231,180 7 September 2000 (07.09.2000) US  
09/752,267 29 December 2000 (29.12.2000) US
- (71) Applicants (*for all designated States except US*): BELL-SOUTH INTELLECTUAL PROPERTY CORPORATION [US/US]; 824 Market Street, Suite 510, Wilmington, DE 19801 (US). STEFANIK, John, R. [US/US]; 5085 Jett Forest Trail NW, Atlanta, GA 30327 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): DURDEN, George, A. [US/US]; 5355 Skidaway Drive, Alpharetta, GA 30022 (US).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHODS AND SYSTEMS FOR CONTROLLING CONSUMER ELECTRONICS EXTERNAL DEVICES VIA DATA DELIVERED TO A DEVICE



(57) Abstract: This document discloses systems and methods for enabling viewers to control and manage programming and to control external consumer electronic devices through the use of a STB or other device. This invention provides command information that is embedded into an EPG signal and transmitted from a headend or transmission facility through a distribution network to the end user. By way of example, the program data includes volume, lighting, internet or environmental tag information for controlling external devices, such as a surround sound entertainment system, home environment system, personal computer, etc. A set top box or other properly configured consumer electronics device either receives data from the external device to effect programming or transmits data to the external device to optimize the viewing experience or to supplement information produced by the EPG.

WO 01/99435 A2

**METHODS AND SYSTEMS FOR CONTROLLING  
CONSUMER ELECTRONICS EXTERNAL  
DEVICES VIA DATA DELIVERED TO A DEVICE**

5                   Cross-Reference to Related Applications

This application claims priority under U.S. law to U.S. serial nos.  
60/213,058, filed June 21, 2000; 60/214,529, filed June 27, 2000; 60/231,180,  
filed September 7, 2000, serial no. 09/752,267, filed December 29, 2000,  
each of which are owned by the assignee of this application and each of  
10 which applications are incorporated in its entirety by this reference.

Technical Field

This invention deals with methods and systems for delivering and  
executing at a Set Top Box ("STB") or other consumer electronic device,  
15 control or program data, whereby the STB interfaces with various external  
devices for sending or receiving instructions or information to those devices.  
Exemplary embodiments are illustrated, including methods and systems for  
supplementing delivered programming with Internet programming via a PC or  
Internet appliance coupled to the STB, controlling environmental equipment  
20 such as home theatre equipment, and managing programming scheduling via  
interface with a personal digital assistant ("PDA").

Background of Invention

Modern cable, satellite, wireless or other communications networks  
25 deliver a host of programming content and other data to viewers' premises,  
each of which generally is outfitted with a STB or Consumer Electronics  
device ("CE device") for decoding and displaying the programming. STBs are  
usually low-cost devices and, due to engineering constraints, presently lack  
the necessary processor speed, memory and components to support Internet  
30 applications or advanced data gathering capabilities. However, many STBs  
do have the capability to communicate with an external device through one of  
several communication mechanisms, such as an IR blaster, serial port,  
modem, or expansion bus peripheral. These communication devices have  
not in the past been used for much more than entering typical scheduling and  
35 control data into the STB, however.

Scheduling has been made easier because part of the programming delivered to STBs are Electronic Program Guides ("EPGs"). These guides provide a viewer with program scheduling information, e.g. a program's channel or other characteristics of the program such as whether the program supports particular protocols like Dolby AC-3 sound, etc. EPGs also can be used to accomplish other useful tasks, such as instructing a STB to tune to a program based on user preferences or instructing a VCR to record a program. Indeed, some EPGs offer the ability to create reminders for program start times. These reminders usually appear as visual alerts on the television screen when the program is about to begin. However, if the user is not watching television at the time these alerts occur, they are of little value.

#### Summary of the Invention

Certain terms used in this section are described more fully below, particularly in the "Terminology" session. This invention aims to provide systems and methods to leverage existing technologies located at a viewer's premises, e.g., the viewer's PC, existing PC Internet connection, STB, and existing EPG data delivery format, to deliver, receive and act upon information and instructions for certain external devices. Exemplary implementations are described where: (1) an STB is connected to a viewer's PC and an application, residing on the STB, retrieves data from the PC using special tags embedded in EPG program data or accesses a host of special Internet related applications while viewing other programming; (2) an STB makes use of information added to or already included in EPG program data to control aspects of the user's home theater environment during a TV program; (3) an STB communicates with an application on a Personal Digital Assistant (PDA) to set reminders about programming, for example, start times, etc. or download program information to the PDA for storage and display, etc.

Program Supplementation: In one embodiment, control tags are inserted into the data stream that provides STBs with the EPG data. An application residing on the STB identifies the control tags, strips them out and processes the instructions therein. The instructions may cause the STB to communicate with a PC, Internet appliance or other computing device that has been coupled to the STB via any of various known communication

mechanisms. The STB thereby can take advantage of the functionality, processing power and display capabilities of the computing device. Using this capability, an STB can supplement its limited capabilities by using the processing power of the PC and the information gathering ability of a PC connected to the Internet. By way of example, tags delivered to the STB may cause it to retrieve Internet data via the user's PC or Internet appliance. That Internet data can be used to supplement EPG data on the STB or display data synchronized to a currently playing event. Alternatively, retrieved Internet data may be stored on the PC for immediate or later viewing.

10        Environmental Control: In another embodiment, the tags embedded in the EPG data stream (or the programming itself) comprise certain control data that correlate to a particular program or event. The control data describes how the user's home theater equipment (e.g., stereo, wall-screen TV, thumpers, scent extractors, etc.) should be optimally controlled during the program presentation. Control data can be used to do such things as  
15        configure home audio equipment to best accommodate a program's soundtrack, adjust TV picture settings, automate room lighting, mute commercials, or even "censor" portions of a TV program.

PDA Interfacing: Many people now carry PDAs, which provide  
20        scheduling and task management capabilities. This invention also provides methods for allowing external devices like PDAs to interface with the STB in order to display alerts or other information concerning programming using the PDA unit's built-in calendar and alarm capabilities. Similarly, the PDA may be configured to send information to the STB application, for example, instructing  
25        it to set reminders for programs or to automatically record programs on a VCR, DVR or other storage medium.

          This invention aims to achieve one, combinations, or all of the following objectives:

- To formulate program control data associated with discrete portions  
30        of programming, which contain information related to controlling presentation of the programming by controlling the manner in which various home theatre or other display and audio devices should be controlled;

- To provide an STB that receives and processes control data and communicates instructions therefrom to external devices coupled to the STB;
  - To formulate control data that describes when and how to access supplemental program data, such as data from an Internet Website, via a user's PC, Internet appliance or other computing device;
  - To provide methods for coupling an STB to a user's PC, Internet appliance or other computing device in order to exchange information and instructions.
- Other objects, advantages and features of this invention will be apparent from review of the remainder of this document, including the drawings.

#### Brief Description of Drawings

Figure 1 is a diagram illustrating an embodiment of a system for controlling a home automated network using EPG tag information according to the present invention.

Figures 2A-C are diagrams illustrating methods of connecting the STB to the home automated network described in Figure 1.

Figure 3 is a diagram illustrating an embodiment of a system for facilitating communications between a STB and a PDA according to the present invention.

Figures 4A-C are diagrams illustrating methods of connecting the STB to the PDA described in Figure 3.

Figure 5 is a diagram illustrating a networked control system, including a PC, according to the present invention.

Figures 6A-E are diagrams illustrating methods for connecting the STB to the PC described in Figure 5.

#### Detailed Description

##### I. Terminology:

Before further describing a particular implementation of the present invention that is shown in the drawings, the following terms are explained, although more thorough understanding of the terms can be reached by

resorting to this entire document. These term explanations are not intended to be conclusive, as technology will change and skilled persons will recognize other ways to implement the same functionality.

- 5       • "Communications network" includes any network or infrastructure that supports communications between multiple devices, including broadband distribution networks, public or private packet-switched or other data networks, including the Internet, or circuit-switched networks such as the public switched telephone network and wireless networks.
- 10       • "Consumer electronics device" or "CE device" is any electronic device or combination of devices capable of receiving, displaying, playing, presenting, recording, deleting, editing, substituting, or disabling audio and/or video content. Exemplary CE devices include: televisions, personal computers, cable set-top boxes,  
15       video cassette recorders, digital video recorders, digital video disc players, compact disc players, and personal computers.
- "Content data" is any information corresponding to at least a portion of a program and related to the content of the program, including content ratings and content attributes, traits, or characteristics.
- 20       • "Control data" is any information corresponding to at least a portion of a program and related to the manner in which the portion may be disabled, modified, replaced, deleted, edited, or otherwise modified by a consumer electronics device, set top box or the like.
- "Program" or "Programming" is any electronic presentation of  
25       information, such as text, audio, video, graphics, or any other form of multimedia, over a communications network. Exemplary programming includes: Internet programming, television broadcasts, cable television programming, pay-per-view programming, video-on-demand, interactive television  
30       programming, satellite programming, and multimedia presentations.
- "Program data" means content or control data or other data associated with or describing the content or manner of presentation of programming.

- "Service provider" is any entity that delivers programs to a program viewer, including cable providers, television broadcasters, satellite providers, and entities supporting Internet World Wide Web ("Web") sites.

5 II. System Overview -- EPG Environmental Control

Briefly, Figures 1, 3 and 5 show system components for delivering data that controls various devices that assist in the optimal presentation of programming. In the subscriber's premises, a Set-Top Box 3 connects through a distribution network 2 to a headend 1. Set-Top Box 3 also  
10 connects to the subscriber's consumer electronic (CE) device 4, for example a VCR, stereo, computer, etc. and/or home automation network 5. The CE device 4 is in turn connected to the Internet through an Internet service provider. As skilled persons will acknowledge, instead of STB 3, the invention could be implemented using software and hardware associated with a CE  
15 Device, such as a TV 8.

A. STB -- CE Device Connection

Set-Top Box 3 can be connected to CE device 4 and/or home automation network 5 through a variety of means. Some detailed examples are listed below. The hardware details of the STB-home theater connection  
20 are provided here for technical reference only and the invention is not limited to such details.

- 1) Using an IR blaster connected to the STB's IR blaster port, the STB may use IR signals to communicate with consumer electronic devices such as a stereo amplifier or a home automation network. (Figures 2A)  
25
- 2) Using the STB's serial port, the STB may connect to a peripheral that converts the RS-232 signals used by the STB into a standard signal used by CE devices and home automation networks. Such signals include signals in the IEEE 1394 (aka: Firewire) or CEBus (Figures 2B) formats.
- 30 3) Using the STB's expansion bus, the STB could be connected to the peripheral described above, as shown in (Figure 2C).

B. Data Tags

Headend 1 houses an EPG Data Server 6 that collects program data

from a data provider. The program data includes information on each TV program such as the program title, start time, duration and description. EPG Data Server 6 sends the program data through distribution network 2 to Set-Top Box 3 located in the subscriber premises. Some of the applications listed in the next section may be accomplished by using information already contained within the EPG data, such as a program's start time and Dolby AC-3 indicator. However, specific control by the EPG must be carried out using special data referred to as "tags," which according to this invention are added to EPG program data to provide more detailed information on controlling the user's home theater environment. The tags instruct the STB application to send control information to specific CE devices and/or home automation networks during the course of a program. For instance, a tag may instruct the STB to configure a stereo amplifier, adjust the TV picture, and dim the lights at the start of a program. A tag may also indicate times at which commercials or possibly objectionable content occurred during a program and send instruction to a TV to mute or blank those portions of the program.

The tags may be added to the EPG data by the EPG data provider or could be added by an optional device in headend 1 referred to as the "Home Control Tag Server" 7. In this latter case, the EPG Data Server 6 sends the EPG data to the Home Control Tag Server 7, which in turn inserts special data referred to as "tags" into the program data for particular TV programs.

Tags may be classified as fixed or variable tags; "Fixed Tags" specify a parameter for the entire length of a program while "Variable Tags" vary a parameter at different times during a program. An example of a variable tag would be one that mutes TV commercials.

The tag would be encoded as a special ASCII string and could include the following elements:

- 1) Command. A command may be an instruction that an applet on the STB send control instructions to specific CE devices and/or a home automation network. For instance, the command could be "Switch Tuner to Dolby Surround Sound."
- 2) Parameters. Each command could have one or more parameters associated with it. For instance, "raise Dolby sound to level 5."



- 3) Start Offset and Duration. A command could have a start offset and duration associated with it to indicate when the command becomes active during the course of a program. (A negative start offset could be used to indicate that the command becomes active before a program begins.) More than one start offset and duration could be provided to make a command active during different portions of a program (e.g. mute commercials).

A detailed example of a possible tag format follows, although many different tag formats and instructions are possible:

`<command [param1, param2,...] >`

-or-

`<OFFSET start1;duration1, [start2;duration2, start3;duration3 ...] >`

`<command [param1, param2,...] >`

`</OFFSET>`

In this example,

- "<>" indicates the beginning and end of a tag.
- "Command" indicates an instruction to the STB application.
- "Param" indicates a parameter associated with the command.
- "OFFSET" and "/OFFSET" is used to indicate that the enclosed command(s) begin at some offset from the beginning of the program.
- "Start" is the starting offset from the beginning of the program.
- "Duration" is the length of time the command is valid from the specified "Start" offset. If Duration is not specified, the command remains in effect until the end of the program or until some other event occurs.

Here are some examples of how this tag format could be used to instruct the STB to configure home audio equipment and lighting for a Pay-Per-View event:

PPV Command: `<LT1 50%> <ST_VOL 20%> <ST_EQU 80,50,60,65,70> <ST_SUR AC3>`

In the PPV Command:

- "LT1", "ST\_VOL", "ST\_EQU", and "ST\_SUR" are instructions to set room lighting, stereo volume, stereo equalization, and stereo surround

sound, respectively when the program begins.

- "50%", "20%", "80,50,60,60,70", and "AC3" are parameters used by each of the above instructions.

Block Command: <OFFSET 00:05:13; 5, 00:19:32; 20> <BLOCK-MUTE PG-13> </OFFSET>

In the Block Command:

- "BLOCK-MUTE" is a command to mute objectionable portions of a program if the user has the option activated.
- "PG-13" is the rating level the user's STB setting would have to match or exceed in order for the muting to take place.
- "00:05:13; 5, 00:19:32; 20" are two different start offset and duration pairs, meaning that the command will be active at two different times during the program.

Tags may be inserted into a variety of places in the program data. A new data field could be created to accommodate the tags or the tags could be added to an existing EPG data field such as the program description. The latter option is optimal since it can use existing EPG data formats such as DVB-SI.

For instance, the tag could be encoded as an ASCII text string and added to the end of a program's description. The STB application would recognize the tag and act on its instructions. However, the STB application would not display the actual tag string to the subscriber when the subscriber displays the program description.

### C. System Capabilities

Using the system described above, a number of control capabilities may be programmed into the EPG data allowing a broadcast provider to offer new and enhanced programming and supplemental products. In addition, users are able to optimize and enhance their television programming. For example, the user could have the ability to adjust, enable or disable any aspect of any application listed below. For instance, the user could disable automatic stereo control for all programs or make it active only for purchased IPPV programs. The following is a listing of some of the enhanced

capabilities of the present invention:

- 5       • Stereo Amplifier Control. The STB application may use existing EPG data or special tags embedded in the program data to adjust a stereo amplifier. For instance, existing EPG data such as a program's AC-3 indicator could be used by the STB application to put the stereo into AC-3 mode during a program. Special tags could be added to program data to do such things as adjust the stereo volume, stereo equalizer, or speaker levels. At the end of the program, stereo settings could be restored to their original or default settings.
- 10       • TV Control. The STB application could use tags embedded in the program data to adjust different aspects of a television set. For instance, tags could adjust picture or sound settings to best accommodate a particular program. At the end of the program, picture or sound settings could be restored to their original or default settings.
- 15       • Lighting Control. The STB application could use existing EPG data such as a program's start and end times or special tags embedded in the program data to control room lighting. For instance, room lights could be set to automatically dim at the start of a purchased IPPV program and then brighten at the end of the program. Also, special  
20       tags could instruct the STB application to brighten room lights during TV commercials, allowing the user to find their way to the kitchen.
- Other Home Automation Control. The STB application could use existing EPG data such as a program's start and end times or special  
25       tags embedded in the program data to control other parts of a home automation network. For example, at the start of a program, the STB application could automatically mute a telephone ringer, adjust window shades, adjust room temperature, or activate a popcorn popper.
- Commercial Mute/Replace. The STB application could use tags  
30       embedded in the program data to mute volume, or tune to a special channel or video input during TV commercials.
- Dynamic Parental Controls. The STB application could use tags embedded in the program data to mute or blank portions of a program

that exceed a certain parental control rating.

- On-Screen Graphics and PIP Display. The STB application could use tags embedded in the program data to enable or disable on-screen displays generated by the STB or some other consumer electronics device. Also, tags could be used to automatically enable, disable or configure a Picture-in-Picture (PIP) display.
- Motion Simulator. The STB application could use tags embedded in the program data to control a motion simulator or a feedback device such as a chair that vibrates.
- Aroma Generator. The STB application could use tags embedded in the program data to control an aroma generator. The aroma generator could generate aromas that correspond to the content of a program.

### III. System Overview- PDA Reminder Exchange

Figure 3 shows system components for connecting the STB to a PDA.

- In the subscriber's premises, a Set-Top Box 3 is connected through a distribution network 2 to a Headend or Transmission Facility 1. Set-Top Box 3 is also connected to the subscriber's Personal Digital Assistant(PDA) 4. An EPG Data Server 5 in the Headend or Transmission Facility 1 provides Set-Top Box 3 with program information on each TV program such as program title, start time, duration and description.

#### A. STB – PDA Connection

- Set-Top Box 3 can be connected to a Personal Digital Assistant 4 through a variety of means. Some detailed examples are listed below. Note that the hardware details of the STB-PDA connection are not the main focus of this invention, which may be implemented over a number of platforms.

- 1) Using an IR blaster connected to the STB's IR blaster port, the STB could send IR signals to a PDA with a built-in IR receiver. Also, the PDA's built-in IR transmitter could be used to send IR signals to the existing IR receiver on the STB for two-way communications. (Figure 4A)
- 2) Using the STB's serial port, the STB could be connected to a data communications port on the PDA. This means of communication would offer two-way data transmission. (Figure 4B)

- 3) Using a peripheral connected to the STB's expansion bus (e.g. an Ethernet card), the STB could be connected to a data communications port on the PDA. This means of communication would offer two-way data transmission. (Figure 4C)

5      B. System Capabilities

A STB application such as an Electronic Program Guide (EPG) would be enhanced to send and receive information to and from a PDA using the system described above. In this embodiment, the following applications could be supported.

- 10      1) Set PDA Reminders. While watching television, the user sets reminders for current or future programming using the enhanced EPG application running on the STB. After program reminders are set, the user positions the PDA in front of the STB's IR blaster (or connects the PDA to the STB via some other hardware configuration, as shown in
- 15      Figures 4A-C, and the enhanced EPG application communicates these reminders to a special application residing on the PDA. The special PDA application adds the program reminder as an entry in the PDA's built-in calendar application. It also configures the calendar application to notify the user with a visual and/or audible alarm before the start of
- 20      the program. Of course, instead of using the PDA's built-in calendar application, the special PDA application may be designed to perform these functions on its own.
- 25      2) Display EPG Info from the STB on the PDA. The enhanced EPG application residing on the STB sends EPG program data to software residing on the PDA for storage and display.
- 30      3) Schedule EPG Reminders or Recordings. After EPG program data has been sent to the PDA, the user sets program reminders and/or schedules program recordings on software residing on the PDA. At some point later in time, the PDA transmits the settings to the enhanced EPG application residing on the STB, which in turn sets program reminders and schedules program recordings within the EPG application.

#### IV. System Overview -- PC InterLink

Briefly, Figure 5 shows a variety of system components for connecting and communicating between a STB and a PC. In the subscriber's premises, Set-Top Box 3 is connected through distribution network 2 to Headend or Transmission Facility 1. Set-Top Box 3 is also connected to the subscriber's Personal Computer (PC) 4. PC 4 is connected to the Internet through an Internet service provider. Of course, instead of STB 3, the invention could be implemented using software and hardware associated with some other CE Device such as a TV, VCR, or DVD Player.

##### 10      A. STB -- PC Connection

Set-Top Box 3 can be connected to Personal Computer 4, in Figure 5, through a variety of means. Some detailed examples are listed below.

- 1) Using the IR blaster port, the STB could communicate with a PC using one of the following two means. These means of communication offer only one-way data transmission at slow speeds.
  - (a) An IR blaster connected to the STB's IR blaster port could send IR signals to an IR receiver peripheral connected to a standard port on a PC. (Figure 6A)
  - (b) The STB's IR blaster port could send electrical signals directly to a peripheral connected to a standard port on a PC. The peripheral would translate the electrical signals sent out via the STB's IR blaster port into signals understood by one of the PC's standard ports. (Figure 6B)
- 2) Using the STB's serial port, the STB could be connected to the PC's serial port. This means of communication would offer two-way data transmission at moderate speeds. (Figure 6C)
- 3) Using a peripheral connected to the STB's expansion bus (e.g. an Ethernet card), the STB could be connected to a standard port on a PC. This means of communication would offer two-way data transmission. (Figure 6D)
- 4) Using the STB's modem phone port, the STB could communicate with a modem connected to the PC. This means of communication would

offer two-way data transmission. (Figure 6E)

#### B. Data Tags

Referring to Figure 5, Headend or Transmission Facility 1 houses an EPG Data Server 6 that collects program data from a data provider. The program data includes information on each TV program such as the program title, start time, duration and description. The EPG Data Server sends the program data to an "Internet Tag Server" 7 that inserts special data referred to as "tags" into the program data for particular TV programs.

The tags act as instructions to a STB application to retrieve Internet data from a PC. Before retrieving this data, the tag could include instructions for presenting the subscriber with different data retrieval options. For instance, a tag in the program data for a baseball game could instruct the STB to display options on the TV screen called "Batter Statistics" and "Pitcher Statistics." If the subscriber selects the "Batter Statistics" option, the tag instructs the STB to retrieve statistics on the current batter from a PC connected to the Internet and display them on the TV screen.

A tag may include the following elements:

- 1) Command. A tag would include a command such as "fetch Internet data from a PC" or "display a menu of data retrieval options to the subscriber." Also, in addition to retrieving Internet data, commands could do other things such as "bookmark a web site on the subscriber's PC." See the "System Capabilities" section below for further examples.
- 2) Command URL. A command could have a URL associated with it. The URL could be a normal Internet URL such as "www.bellsouth.com" or, to save memory, the URL could be represented in some shorthand notation, e.g. "wbis", understood by the STB or PC applications.
- 3) Command Parameters. A tag command could have one or more parameters associated with it. For example, the command to display a menu of data retrieval options to the subscriber could have a parameter that indicates the format that the menu options are to be displayed in. Another parameter might indicate when the menu should be displayed. For instance, a menu could be displayed while the subscriber is watching the TV program or when the subscriber calls up

EPG information on the program.

4) Menu Option Names. A tag could list the names of menu options to be displayed to the subscriber.

5) Menu Option Actions. A tag could include instructions on what to do if the subscriber selects a particular menu option. For instance, an action might be to retrieve and display a specific type of data from an Internet site.

6) Menu Option Parameters. A tag could include parameters for a menu option. For instance, a parameter could instruct the STB application on how to display results when a menu option is selected.

A detailed example of a possible tag format follows, although many different tag formats and instructions are possible.

```
<command URL [param1, param2,...] >
  [<menuoption1 action1 [param1,param2,...]>,
  < menuoption2 action2 [param1,param2,...]>
  ...
</command>]
```

Here is an example of how the tag format could be used to present the subscriber with menu options and retrieve supplemental EPG data for the movie "The Matrix". The following represents an embedded command for that movie:

```
<DISPMENU wbls/matrix descript,buttons1>
  <"Director Bio" DispData=director box1>
  <"Cast Notes" DispData=cast box1>
</DISPMENU>
```

In this example,

- "DISPMENU" is a command to display menu options for the program
- "wbls/matrix" is shorthand notation for a special web URL setup to provide data for the program. In this example, "wbls/matrix" is shorthand notation for the web URL "www.bellsouthmovies.com/matrix".
- "descript,buttons1" are command parameters. In this example, "descript"



indicates that the menu should be displayed when the subscriber calls up the program's description box, and "buttons1" indicates a standard format in which to display the menu options.

- "Director Bio" and "Cast Notes" are the names of the menu options to display to the subscriber.
- "DispData=director" and "DispData=cast" are the actions the STB application should take when the subscriber selects the menu options. In these cases, the STB application will retrieve data on the director or cast notes from the web URL "wbis/matrix" ("www.bellsouthmovies.com/matrix").
- "box1" indicates the format in which to display the resulting data.

Tags can be inserted into a variety of places in the program data. A new data field could be created to accommodate the tags or the tags could be added to an existing EPG data field such as the program description. The latter option is optimal since it can use existing EPG data formats such as DVB-SI. For instance, the tag could be encoded as an ASCII text string and added to the end of a program's description. The STB application would recognize the tag and act on its instructions. However, the STB application would not display the actual tag string to the subscriber when the subscriber displays the program description.

#### C. System Capabilities

Using the system described above, the following capabilities could be supported:

- 1) Supplemental program information. Existing EPG data for a current or future event is supplemented by data retrieved from a PC attached to the Internet. The additional data can be displayed on the TV screen as part of the EPG data or displayed on the PC screen in a special window. Multiple options may be presented. For example, the STB application may display a menu giving the subscriber the ability to retrieve data on a show's cast or call up trivia on the particular episode.
- 2) Real-time data. Data is synchronized to a currently playing event. For instance, current pitcher and batter statistics could be provided during

a baseball game. The STB application could present a menu in the bottom corner of the screen allowing the subscriber to display statistics on either the pitcher or batter. If the subscriber selects an option, the STB application requests the information from the PC. The PC, in turn, visits a special web site that provides data that is specially formatted and synchronized to a TV channel being viewed. The statistics on the current pitcher or batter are then displayed in a window (e.g., a picture in picture or PIP window) on the TV screen.

- 3) PC browsing. The STB application allows the subscriber to display related data on a current or future event on the subscriber's PC. The data could be displayed on the PC in several different ways. For instance, the data could be part of a web page that is automatically called up in a web browser such as Netscape. The data could also be stored on the PC for later viewing.
- 4) Automated bookmarks. Instead of going ahead and displaying a related web page on the PC, the STB application could instruct the PC to store a web page as a bookmark for later viewing.
- 5) Purchasing. The STB application allows the subscriber to purchase products related to a current or future event over the Internet. While the STB application would initiate the purchase, the complete purchase process could take place on the STB or the PC.
- 6) Calendar reminder. The STB application could instruct the PC to add the name and start time of an event to a calendar application on the PC. The calendar application would alert the subscriber to when an event begins. The calendar application could interface with a personal digital assistant such as a Palm Pilot, etc. by downloading information when the PDA is synchronized with the calendar function on the PC.
- 7) Printing. The STB application could send event information to a PC and instruct the PC to print the event information on a printer.
- 8) Screen capture. The STB application could send a screen capture to the PC for use in a variety of PC applications.
- 9) Bill review. The STB application could instruct the PC to retrieve the

subscriber's billing information from the Internet for display on the TV or PC.

10) Interactive help. The STB application could instruct the PC to retrieve interactive help from the Internet for display on the TV or PC.

5        While this invention has been described in conjunction with specific  
embodiments, it is evident that many alternatives, modifications, and  
variations will be apparent to those skilled in the art. Accordingly, the  
preferred embodiments of the present invention that are here described are  
intended to be illustrative and not limiting. Various changes may be made  
10 without departing from the true spirit and full scope of the invention as defined  
in the following claims.

What is claimed is:

- 1 1. A method for obtaining information related to broadcast programming,  
2 the method comprising:
  - 3 a. adding at least one data tag to electronic program guide (EPG)  
4 data, wherein the at least one data tag contains detail control  
5 information relating to broadcast programming, the data tag  
6 consisting of one or more of the following elements: (1) a command,  
7 (2) at least one parameter, (3) command URL (4) menu option  
8 names, (5) menu option actions, (6) menu option parameters, and  
9 (7) a start offset and duration;
  - 10 b. transmitting the EPG data and the at least one data tag to a viewer;
  - 11 c. receiving the transmitted EPG data and the at least one data tag by  
12 the viewer;
  - 13 d. using the at least one data tag to obtain related programming  
14 information from the internet.
- 1 2. The method of claim 1, in which the using the at least one data tag  
2 further comprises using the at least one data tag to obtain  
3 supplemental electronic program guide data from the internet for  
4 current or future programming events.
- 1 3. The method of claim 1, in which the using the at least one data tag  
2 further comprises using the at least one data tag to obtain real-time  
3 data from the internet that is synchronized to the program.
- 1 4. The method of claim 1, in which the using the at least one data tag  
2 further comprises using the at least one data tag to link to at least one  
3 website that contains related information to the program.
- 1 5. The method of claim 1, further comprising displaying the related  
2 program information.
- 1 6. The method of claim 5, wherein the related data is displayed on a

2 computer.

1 7. The method of claim 5, wherein the related data is displayed  
2 simultaneously with the program on a consumer electronic device.

1 8. The method of claim 5, further comprising purchasing the program  
2 using the internet.

1 9. The method of claim 1, further comprising storing the related  
2 information in a storage device for later retrieval.

1 10. A method for using electronic program guide (EPG) data for  
2 programming and monitoring broadcast events, the method  
3 comprising:  
4 a. receiving EPG data on a consumer electronic device, wherein  
5 the data comprises (1) content data, (2) control data, or (3) both  
6 content and control data;  
7 b. interfacing the consumer electronic device with a personal digital  
8 assistant (PDA);  
9 c. communicating between the PDA and CE.

1 11. The method of claim 10, in which interfacing further comprises using a  
2 serial cable interface to connect the CE and the PDA.

1 12. The method of claim 10, in which interfacing further comprises using an  
2 inferred blaster interface to connect the CE and PDA.

1 13. The method of claim 10, in which interfacing further comprises using an  
2 expansion bus interface to connect the CE and PDA.

1 14. The method of claim 10, in which the communicating comprises using  
2 the PDA to program the CE to automatically record a programming  
3 event.

- 1 15. The method of claim 10, further comprising downloading at least one  
2 portion of the EPG data to the PDA, wherein the downloaded  
3 information is used by the PDA to monitor a schedule of programming  
4 events.
- 1 16. A method for controlling and managing the presentation of programs  
2 the method, comprising:  
3 a. adding at least one data tag to electronic program guide (EPG)  
4 data, wherein the at least one data tag contains detail control  
5 information relating to broadcast programming, the data tag  
6 consisting of one or more of the following elements: (1) a command,  
7 (2) at least one parameter, and (3) a start offset and duration;  
8 b. transmitting the EPG data and the at least one data tag to a viewer;  
9 c. receiving the EPG data and the at least one data tag;  
10 d. presenting a program associated with the at least one data tag at  
11 the viewer's location;  
12 e. using the at least one data tag to control the presentation of a  
13 program; and  
14 f. modifying the presentation of the program in real-time using the at  
15 least one data tag.
- 1 17. The method of claim 16, wherein using the at least one data tag further  
2 comprises using an inferred blaster interface to transmit the at least  
3 one data tag between a first and a second consumer electronic device.
- 1 18. The method of claim 16, wherein using the at least one tag data further  
2 comprises using a serial interface to transmit the at least one data tag  
3 between a first and a second consumer electronic device.
- 1 19. The method of claim 16, wherein using the at least one tag data further  
2 comprises using an expansion bus interface to transmit the at least one  
3 data tag between a first and a second consumer electronic device.
- 1 20. The method of claim 16, in which modifying the presentation further

- 2 comprises modifying the volume of the program based upon the at  
3 least one data tag.
- 1 21. The method of claim 16, in which modifying the presentation further  
2 comprises modifying the program presentation during commercials.
- 1 22. The method of claim 21, in which modifying the program presentation  
2 during commercials comprises muting the volume.
- 1 23. The method of claim 21, in which modifying the program presentation  
2 during commercials comprises automatically displaying alternate  
3 programming during the commercial.
- 1 24. The method of claim 16, further comprising modifying the viewing  
2 environment.
- 1 25. The method of claim 24, in which modifying the viewing environment  
2 further comprises modifying the room lighting based upon the at least  
3 one data tag.
- 1 26. The method of claim 24, in which modifying the viewing environment  
2 further comprises controlling a motion simulator using the at least one  
3 data tag associated with the program being displayed.
27. The method of claim 24, which modifying the viewing environment  
further comprises operating a aroma generator to generate aromas that  
correspond to the content of the program using the at least one data  
tag.






Figure 2A: IR Interface




Figure 2B: RS-232 Serial Interface




Figure 2C: Expansion Bus Interface




Figure 3




Figure 4A: IR Interface




Figure 4B: RS-232 Serial Interface




Figure 4C: Expansion Bus Interface




Figure 5: System Overview




Figure 6A: IR Blaster to IR Receiver Interface




Figure 6B: Blaster Port Translator Interface




Figure 6C: RS-232 Serial Interface




Figure 6D: Expansion Bus Interface





Figure 6E: Modem Interface



\*Examples of a standard PC port include RS-232, USB, Centronics, SCSI, Firewire or Ethernet.

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number  
WO 01/099435 A3

(51) International Patent Classification<sup>7</sup>: H04N 5/00

A. [US/US]; 5355 Skidaway Drive, Alpharetta, GA 30022 (US).

(21) International Application Number: PCT/US01/08465

(22) International Filing Date: 16 March 2001 (16.03.2001)

(74) Agents: PRATT, John, S. et al.; KILPATRICK STOCKTON LLP, 1100 Peachtree Street, Suite 2800, Atlanta, GA 30309-4530 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/213,058 21 June 2000 (21.06.2000) US  
60/214,529 27 June 2000 (27.06.2000) US  
60/231,180 7 September 2000 (07.09.2000) US  
09/752,267 29 December 2000 (29.12.2000) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicants (*for all designated States except US*): BELL-SOUTH INTELLECTUAL PROPERTY CORPORATION [US/US]; 824 Market Street, Suite 510, Wilmington, DE 19801 (US). STEFANIK, John, R. [US/US]; 5085 Jett Forest Trail NW, Atlanta, GA 30327 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


Published:

(75) Inventor/Applicant (*for US only*): DURDEN, George,

— with international search report

[Continued on next page]

(54) Title: METHODS AND SYSTEMS FOR CONTROLLING CONSUMER ELECTRONICS EXTERNAL DEVICES VIA DATA DELIVERED TO A DEVICE



(57) Abstract: This document discloses systems and methods for enabling viewers to control and manage programming and to control external consumer electronic devices through the use of a STB or other device. This invention provides command information that is embedded into an EPG signal and transmitted from a headend or transmission facility through a distribution network to the end user. By way of example, the program data includes volume, lighting, internet or environmental tag information for controlling external devices, such as a surround sound entertainment system, home environment system, personal computer, etc. A set top box or other properly configured consumer electronics device either receives data from the external device to effect programming or transmits data to the external device to optimize the viewing experience or to supplement information produced by the EPG.

WO 01/099435 A3



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:  
3 October 2002



<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 7 H04N5/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 7 H04N		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, PAJ		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 04561 A (SCHOAFF P CHRISTOPHER ;ALEXANDER RON (US); GUIDE E INC (US); HANCO) 28 January 1999 (1999-01-28) page 10, line 1 - line 35 page 22, line 20 -page 23, line 33 claims 17-25	1,2,4-7, 9
Y	---	3
X	US 5 818 935 A (MAA CHIA-YIU) 6 October 1998 (1998-10-06) abstract column 7, line 43 - line 50 column 10, line 11 - line 22 column 10, line 35 - line 65 column 19, line 33 - line 61 ---	1-8
-/--		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the international search  9 July 2002		Date of mailing of the international search report  19. 07. 2002
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer  Fantini, F

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 13368 A (BRIEN SEAN ANDREW O ;MILNES KENNETH ALAN (US); SCHEIN STEVEN MICHA) 10 April 1997 (1997-04-10) abstract page 4, line 37 -page 6, line 17 page 17, line 15 - line 18 page 20, line 19 - line 36 figures 10,11 ---	1-7
Y	WO 00 20976 A (HOTV INC) 13 April 2000 (2000-04-13) page 34, line 3 - line 22 figure 12 ---	3
A	---	1,6,7
A	KATE TEN W ET AL: "TRIGG & LINK A NEW DIMENSION IN TELEVISION PROGRAM MAKING" PROCEEDINGS OF THE EUROPEAN CONFERENCE ON MULTIMEDIA APPLICATIONS,SERVICES AND TECHNIQUES, XX, XX, May 1997 (1997-05), pages 51-65, XP000668931 the whole document ---	1-9
X	WO 98 16062 A (CHANG ALLEN) 16 April 1998 (1998-04-16) abstract page 4, line 14 - line 19 page 5, line 4 - line 17 page 6, line 33 -page 7, line 7 figure 3 ---	10-15
A	EP 0 952 734 A (IBM) 27 October 1999 (1999-10-27) abstract column 4, line 43 -column 5, line 3 column 5, line 24 - line 39 column 6, line 25 - line 38 column 9, line 10 - line 27 ---	10-15
A	US 5 671 267 A (GREWE ANTHONY JAMES ET AL) 23 September 1997 (1997-09-23) the whole document ---	10-15
A	US 5 668 591 A (SHINTANI PETER) 16 September 1997 (1997-09-16) the whole document ---	10-15
Y	WO 98 47286 A (JOHNSON MICHAEL WAYNE ;HAILEY JAMES EDWIN (US); THOMSON CONSUMER E) 22 October 1998 (1998-10-22) page 10, line 21 - line 33 page 22, line 6 - line 11 page 25, line 11 - line 26 ---	16-27
	--- -/--	

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 398 070 A (LEE DONG H) 14 March 1995 (1995-03-14) abstract column 2, line 55 -column 3, line 20 column 4, line 12 - line 24 column 4, line 47 -column 5, line 40 figure 3 -----	16-27
A	EP 0 508 939 A (GOMES DOS SANTOS ALCINO) 14 October 1992 (1992-10-14) the whole document -----	16-27

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 01/08465**Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)**

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

**Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)**

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-9

Use of control data to communicate with an Internet appliance. Internet data can be used to supplement EPG data on the STB or display data synchronised to a currently playing event.

2. Claims: 10-15

Use of EPG data to interface a PDA with the STB in order to display alerts or other information concerning programming (using the PDA unit's built-in calendar and alarm capabilities).

3. Claims: 16-27

Use of control data to describe how the user's home-theater equipment (e.g stereo, wall-screen TV, thumpers, scent extractors, etc.) should be optimally controlled during the program presentation.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9904561	A	28-01-1999	AU 733993 B2 31-05-2001
		AU 8504898 A	10-02-1999
		BR 9812104 A	18-07-2000
		CN 1290452 T	04-04-2001
		EP 1036466 A1	20-09-2000
		JP 2001513595 T	04-09-2001
		US 6122011 A	19-09-2000
		US 2002073424 A1	13-06-2002
		WO 9904561 A1	28-01-1999
		US 6177931 B1	23-01-2001
		US 6217435 B1	17-04-2001
US 5818935	A	06-10-1998	NONE
WO 9713368	A	10-04-1997	AU 7387196 A 28-04-1997
		BR 9611064 A	13-07-1999
		CA 2232003 A1	10-04-1997
		CN 1200221 A	25-11-1998
		EP 0880856 A1	02-12-1998
		JP 10512420 T	24-11-1998
		US 2002059599 A1	16-05-2002
		WO 9713368 A1	10-04-1997
		US 6263501 B1	17-07-2001
		US 6388714 B1	14-05-2002
		US 6002394 A	14-12-1999
		US 6323911 B1	27-11-2001
		US 6075575 A	13-06-2000
		US 2002019981 A1	14-02-2002
WO 0020976	A	13-04-2000	AU 6294399 A 26-04-2000
		WO 0020976 A2	13-04-2000
		US 2001023436 A1	20-09-2001
WO 9816062	A	16-04-1998	AU 4896397 A 05-05-1998
		CN 1237308 A	01-12-1999
		EP 0931415 A1	28-07-1999
		JP 2001511958 T	14-08-2001
		WO 9816062 A1	16-04-1998
EP 0952734	A	27-10-1999	AU 3653699 A 08-11-1999
		CA 2328948 A1	28-10-1999
		CN 1234687 A	10-11-1999
		EP 0952734 A2	27-10-1999
		EP 1075667 A1	14-02-2001
		JP 2000041198 A	08-02-2000
		TW 411709 B	11-11-2000
		WO 9954768 A1	28-10-1999
US 5671267	A	23-09-1997	CA 2165705 A1 01-07-1996
US 5668591	A	16-09-1997	JP 7271697 A 20-10-1995
		GB 2288044 A , B	04-10-1995
WO 9847286	A	22-10-1998	AU 4496597 A 11-11-1998
		AU 4496797 A	11-11-1998
		AU 4496897 A	11-11-1998
		AU 4590397 A	11-11-1998
		AU 4590497 A	11-11-1998

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9847286	A		AU 4650297 A	11-11-1998
			AU 5601398 A	11-11-1998
			BR 9714607 A	23-05-2000
			BR 9714608 A	23-05-2000
			BR 9714609 A	23-05-2000
			BR 9714684 A	25-07-2000
			BR 9714685 A	25-07-2000
			CN 1253697 A	17-05-2000
			CN 1255210 A	31-05-2000
			CN 1256840 A	14-06-2000
			CN 1256841 A	14-06-2000
			CN 1256842 A	14-06-2000
			CN 1256843 A	14-06-2000
			CN 1269101 A	04-10-2000
			EP 0976244 A1	02-02-2000
			EP 0976245 A1	02-02-2000
			EP 0976246 A1	02-02-2000
			EP 1040664 A1	04-10-2000
			EP 0976247 A1	02-02-2000
			EP 0976248 A1	02-02-2000
			EP 0976023 A1	02-02-2000
			GB 2340690 A , B	23-02-2000
			JP 2001520825 T	30-10-2001
			JP 2001520826 T	30-10-2001
			JP 2002514371 T	14-05-2002
			JP 2001520827 T	30-10-2001
			JP 2002512753 T	23-04-2002
			JP 2001523406 T	20-11-2001
			JP 2002514328 T	14-05-2002
			TR 9902422 T2	21-03-2000
			TR 9902429 T2	21-03-2000
			TR 9902479 T2	21-04-2000
			TR 9902511 T2	21-03-2000
			WO 9847283 A1	22-10-1998
			WO 9847284 A1	22-10-1998
			WO 9847285 A1	22-10-1998
			WO 9847286 A1	22-10-1998
			WO 9847287 A1	22-10-1998
			WO 9847288 A1	22-10-1998
			WO 9847063 A1	22-10-1998
US 5398070	A	14-03-1995	KR 9604813 B1	13-04-1996
EP 0508939	A	14-10-1992	PT 97283 A	30-06-1992
			EP 0508939 A2	14-10-1992